

GLOBE KLEEN | 2002™

Viscous Polymer, Resin
& Coating Remover

ENVIRONMENTAL

- ⌀ Reduced VOC
- ⌀ Non-Hazardous
- ⌀ Non-Flammable
- ⌀ Non-Toxic
- ⌀ DOES NOT contain raw materials known to the State of California (Prop 65) to cause cancer, birth defects or other reproductive harm
- ⌀ DOES NOT contain raw materials listed on SECTION 112(b) of HAPs List
- ⌀ No SARA 313 Ingredients
- ⌀ REACH Compliant

GLOBE KLEEN | 2002™ is a mixture of organic solvents, wetting agent and a corrosion inhibitor. It easily **adheres to vertical and horizontal substrates.** Ideal for **Spray Foam Contractors** - cleaning Spray Foam and Coatings Equipment. **Manufacturers** - removing Diisocyanates lines, metering equipment feed lines, etc., **OEM** - Automotive, Aerospace, Injection Mold, Foam Sheathing Insulation, and Cushioning.

Effectively Removes at room temperature;

- ⌀ **Polymers** - Over Spray Polyurethane Foam, cured urethane foam deposits and build-up from mixing heads, troughs, conveyor parts, side walls, floors, rollers, foam cutting devices and molds
- ⌀ **Resins** - Industrial Resins, Epoxy, Polyester, Vinylester, Polyamide, High and Low Solid Aliphatic Resins,

Viscous Polymer, Resin & Coating Remover

and Waterborne Epoxy Primers

- ⌀ **Coatings** - Polyurea, Polyurethane Acrylic, Varnish and Alkyl Enamel
- ⌀ **Adhesives** - Cured Polyurethane Reactive Hot Melt Urethane Adhesives and Silicone

Features & Benefits

- ⌀ Low VOC
- ⌀ High soil loading
- ⌀ **Replaces NMP, BLO, Acetone, Methylene Chloride, MEK, PM Acetate and 1,1,1 Trichloroethane**
- ⌀ Low rate of evaporation
- ⌀ **Multi substrate** - Safe of most Ferrous and non-Ferrous Metals
- ⌀ **Compatible** and Non-Corrosive on various metals, plastics, glass and ceramics

Application

Use **Full Strength (Do NOT add water)** at room temperature by **BRUSH** or **ROLLER**. Once soils are dissolved, scrape off. Parts can be wiped with a damp cloth or rinsed off with warm water.

Use Natural Rubber Gloves when handling this product. Do not Heat or Atomize this product.

For hand wipe applications, use **NZD ISO FLUSH™**
GO GREEN™ Wipes.



TYPICAL PROPERTIES

Appearance:	Clear Amber Liquid
Flash Point: (Pensky-Martens closed cup)	169 °F
Odor:	Mild Organic Ester
pH (50% solution in water @ 68°F)	6.8 - 7.8
Vapor Pressure: (components)	0.20 - 0.90 mmHg @ 20 °C (68 °F)
Viscosity (Centipoise @ 68 °F): (Brookfield Spindle #3, 10 RPM)	4000-5000
Initial boiling point/ boiling range (@ 760 [mm Hg])	356 - 396 °F
Ideal Operating Temp (°F)	Room Temperature
Ideal Operating Concentration	Full Strength
Specific Gravity @ (68°F)	0.9835 - 0.9924
Weight/Gal. (lbs. /gal.)	8.40 - 8.45
VOC Content: (ASTM D-2369, Method 24)	3.85 lbs./gal or 437 grams/liter
HMIS Rating:	Health = 2 Fire = 2 Reactivity = 0
Product #	02-W209570

**RECOMMENDED MATERIALS TO USE FOR:
O-Rings, Gaskets, Hoses and Pump Packaging**

Teflon
Butyl Rubber
Silicon Rubber
Klarez

Mild Steel
Halar
Melamine
Nylon 101

Polyethylene
Polypropylene
Ryton

Viton
ABS
Durel
Kynar

Phenolic
Polyurethane
PVC
Buna-N

MATERIAL TO AVOID

PET
Lexan
Valox
Polyester

Noryl EN-265
Noryl -73 I
Polysulfone
Ultem

Lucite
Hypalon

PACKAGING & STORAGE

HDPE UN Rated

- 1 Gallon EasyPour Jugs
- 5 Gallon Pails
- 55 Gallon Steel Drums (closed cap)

Freight easily shipped via local carriers ground or LTL.

This product should be kept in its original container above freezing and less than 100 °F.

Store drums in a dry area.

SAFETY&HANDLING PRECAUTIONS

Refer to SDS for additional safe handling & disposal

Direct contact of **GLOBE KLEEN | 2002™ Viscous Polymer, Resin & Coating Remover** will cause a mild skin irritation or serious eye irritation. It is important to utilize recommended gloves (natural rubber), safety goggles and other suitable protective clothing your company recommends. Aspiration hazard if swallowed. Keep liquid and vapor away from heat, sparks and flames. Keep container closed. **Use product with adequate ventilation. Do Not take internally.** Keep out of reach of children. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Never give anything by mouth to an unconscious person Get medical advice/attention.

Refer to SDS Section 4 First Aid Measures

DISPOSAL

Refer to SDS for additional safe handling & disposal

The spent material should not be disposed of in any sewerage system. Solutions containing hazardous or non-hazardous coatings and other soils should be handled and treated according to Federal, State and Local Environmental Laws. Discharge your waste and rinse water according to Federal, State and Local Regulations.



10 Eagle Avenue - Suite 500 - Mount Holly, NJ 08060
Phone: 609-518-7577 / Fax: 609-518-5277