

ENVIRONMENTAL

- ⊗ Reduced VOC
- ⊗ Non-Hazardous
- ⊗ Non-Flammable
- ⊗ Non-Toxic
- ⊗ DOES NOT contain raw materials on the NJ Community Right to Know Environmental Hazardous Substance (EHS) List
- ⊗ DOES NOT contain raw materials known to the State of California (Prop 65) to cause cancer, birth defects or other reproductive harm
- ⊗ DOES NOT contain raw materials listed on SECTION 112(b) of HAPs List
- ⊗ No SARA 313 Ingredients
- ⊗ REACH Compliant

StripMore™ Paint & Coating Remover

An Environmentally Safe, low odor Immersion Paint & Coating Remover used in all cleaning application equipment including OEM Metal Components, Reject Components, Paint Lines, Spray Guns, Circulating Systems, Reactors, Mixing Tanks, Cups, Industrial Floors, and Surfaces. StripMore™ Paint & Coating Remover offers a significant reduction in “VOC” Volatile Organic Compounds and is a **powerful REPLACEMENT for NMP-based paint strippers**, as well as other hazardous solvents such as Phenol, Methylene Chloride, Methanol, MEK, PM Acetate, Acetone, Aromatic and Aliphatic Hydrocarbons.

It effectively dissolves and removes both aqueous and solvent-based coatings, primers, lacquers, inks, varnishes, adhesives, latex, rubbers, resins, electrophoretic deposits, and pigmented gel coats.

In addition, StripMore™ Paint & Coating Remover removes live “uncured” Industrial Coatings, Polymers & Resins such as Polyurea Spray Coatings “Polyurethane”, Isocyanates, Polyester, Vinylester, Polyamide, and epoxy, as well as High-Performance Adhesives such as Cyanoacrylates, Silicones, two-components PU Silicones, and Reactive Hot Melt Polyurethane.

Features & Benefits

- ⊗ Low VOC
- ⊗ Low rate of evaporation
- ⊗ High Paint loading
- ⊗ Recyclable via vacuum distillation - resulting in reduced disposal costs
- ⊗ Residue Free
- ⊗ **Replaces NMP based paint strippers, Phenol**, Methylene Chloride, Methanol, MEK, PM Acetate, Acetone, Aromatic and Aliphatic Hydrocarbons.

Application

Use Full Strength at room temperature (Do Not Add Water) in an immersion tank. For hand wipe application use **StripMore™ Paint & Coating Remover GO GREEN™ Wipes**.

Use Natural Rubber Gloves when handling this product.



TYPICAL PROPERTIES

Appearance:	Clear Amber Liquid
Flash Point: (Pensky-Martens closed cup)	169 °F
Odor:	Mild Organic Ester
Surface Tension:	24 (dynes/cm 24) (water = 1.0)
pH (50% solution in water @ 68°F)	6.8 - 7.8
Vapor Pressure: (components)	0.20 - 0.90 mmHg @ 20 °C (68 °F)
Initial boiling point/ boiling range (@ 760 [mm Hg])	356 - 396 °F
Ideal Operating Temp (°F)	Room Temperature or maximum heated to 140 °F
Ideal Operating Concentration	Full Strength
Specific Gravity @ (68°F)	0.980 - 0.984
Weight/Gal. (lbs. /gal.)	8.20
VOC Content: (ASTM D-2369, Method 24)	3.85 lbs./gal or 437 grams/liter
HMIS Rating:	Health = 2 Fire = 2 Reactivity = 0
Product #	02-W129562

**RECOMMENDED MATERIALS TO USE FOR:
O-Rings, Gaskets, Hoses and Pump Packaging**

Teflon
Butyl Rubber
Silicon Rubber
Klarez

Mild Steel
Halar
Melamine
Nylon 101

Polyethylene
Polypropylene
Ryton

Viton
ABS
Durel
Kynar

Phenolic
Polyurethane
PVC
Buna-N

MATERIAL TO AVOID

PET
Lexan
Valox
Polyester

Noryl EN-265
Noryl -73I
Polysulfone
Ultem

Lucite
Hypalon

PACKAGING & STORAGE

HDPE UN Rated

- 1 Gallon EasyPour Jugs
- 5 Gallon Pails
- 55 Gallon Steel Drums (closed cap)

GO GREEN™ Wipes
in an "Easy Carry Bucket"
(90 / 12" x 12" Polypropylene
Saturated Wipes)

Freight easily shipped via local
carriers ground or LTL.

This product should be kept in its
original container above freezing
and less than 100 °F.

Store drums in a dry area.

SAFETY&HANDLING PRECAUTIONS

Refer to SDS for additional safe
handling & disposal

Direct contact of **StripMore™ Paint & Coating Remover** cause a **mild skin irritation or serious eye irritation**. It is important to utilize recommended gloves (natural rubber), safety goggles and other suitable protective clothing your company recommends. Aspiration hazard if swallowed. Keep liquid and vapor away from heat, sparks and flames. Keep container closed.

Use product with adequate ventilation. Do Not take internally. Keep out of reach of children. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Never give anything by mouth to an unconscious person Get medical advice/attention.

Refer to SDS Section 4 First Aid Measures

DISPOSAL

Refer to SDS for additional safe
handling & disposal

The spent material should not be disposed of in any sewerage system. Solutions containing hazardous or non-hazardous coatings and other soils should be handled and treated according to Federal, State and Local Environmental Laws. Discharge your waste and rinse water according to Federal, State and Local Regulations.



10 Eagle Avenue - Suite 500 - Mount Holly, NJ 08060
Phone: 609-518-7577 / Fax: 609-518-5277