

SURF XTM PRO 2000

Gun Flush



Keep Your Gun CLEAN, GREEN and MEAN

ENVIRONMENTAL

- ⊕ Reduced VOC
- ⊕ Non-Flammable
- ⊕ Non-Hazardous
- ⊕ Non-Toxic
- ⊕ None of the Ingredients are listed on (CA PROP 65)
- ⊕ No SARA 311, 312, 313 Ingredients
- ⊕ Non HAPs
- ⊕ DOES NOT contain raw materials on the NJ Community Right to Know Environmental Hazardous Substance List
- ⊕ REACH Compliant

A safe and eco-friendly flushing liquid that can be used with all types of spray guns that are used for applying Spray Foam, Resin, Paint, and coatings. **SURF XTM PRO 2000 Gun Flush** effectively removes the build-up of foam, liquid or hardened Isocyanates, Polyol Coatings (Polyurea), Silicon, Resin (Epoxy, Polyester, and Vinyl Ester) and Adhesives, ensuring a smooth and even spray throughout the day. Improving productivity and performance.

It is recommended to use this product on a daily basis to keep your gun mix chamber clean and clear



Directions:

- Turn off both A and B lines.
- Insert the canister filled with **SURF XTM PRO 2000 Gun Flush** into the gun.
- Pull the trigger several times to prime **SURF XTM PRO 2000 Gun Flush** into the pump.
- Spray onto cardboard to see **SURF XTM PRO 2000 Gun Flush** released into the gun mix chamber and build-up dissolved.
- Turn on both A and B lines and squeeze the trigger until you see **SURF XTM PRO 2000 Gun Flush** spraying out of the gun.
- You are now ready to continue spraying.
- ***When you notice an uneven spray pattern or need to clean your gun, use this method to maintain a clean chamber for future use.***

**RECOMMENDED MATERIALS TO USE FOR:
O-Rings, Gaskets, Hoses and Pump Packaging**

Teflon
Butyl Rubber
Silicon Rubber
Klarez

Mild Steel
Halar
Melamine
Nylon 101

Polyethylene
Polypropylene
Ryton

Viton
ABS
Durel
Kynar

Phenolic
Polyurethane
PVC
Buna-N

MATERIAL TO AVOID

PET
Lexan
Valox
Polyester

Noryl EN-265
Noryl -731
Polysulfone
Ultem

Lucite
Hypalon

TYPICAL PROPERTIES

Appearance:	Clear Liquid
Flash Point: (Pensky-Martens closed cup)	169 °F
Odor:	Mild Organic Ester
Surface Tension:	24 (dynes/cm 24) (water = 1.0)
pH (50% solution in water @ 68°F)	6.8 - 7.8
Vapor Pressure: (components)	0.20 - 0.90 mmHg @ 20 °C (68 °F)
Initial boiling point/ boiling range (@ 760 [mm Hg])	356 - 396 °F
Ideal Operating Temp (°F)	Room Temperature or maximum heated to 140 °F
Ideal Operating Concentration	Full Strength
Specific Gravity @ (68°F)	0.980 - 0.984
Weight/Gal. (lbs. /gal.)	8.20
VOC Content: (ASTM D-2369, Method 24)	3.85 lbs./gal or 437 grams/liter
HMIS Rating:	Health = 2 Fire = 2 Reactivity = 0
Product #	02-W189569

SAFETY & HANDLING PRECAUTIONS

Refer to SDS for additional safe handling & disposal

Direct contact of **SURF X™ PRO 2000 Gun Flush** will cause a mild skin irritation or serious eye irritation. It is important to utilize recommended gloves (natural rubber), safety goggles and other suitable protective clothing your company recommends. Aspiration hazard if swallowed. Keep liquid and vapor away from heat, sparks and flames. Keep container closed. **Use product with adequate ventilation.** **Do Not take internally.** Keep out of reach of children. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Never give anything by mouth to an unconscious person. Get medical advice/attention.

Refer to SDS Section 4 First Aid Measures

DISPOSAL

Refer to SDS for additional safe handling & disposal

The spent material should not be disposed of in any sewerage system. Solutions containing hazardous or non-hazardous coatings and other soils should be handled and treated according to Federal, State and Local Environmental Laws. Discharge your waste and rinse water according to Federal, State and Local Regulations.

PACKAGING

32 oz. Clear HDPE clear plastic bottle with an EasyPour Push Pull Cap.

Case of 6 or 36 Quarts

This product should be kept in its original container above freezing and less than 100 °F. Store in a dry area.



10 Eagle Avenue - Suite 500 - Mount Holly, NJ 08060
Phone: 609-518-7577 / Fax: 609-518-5277