



Global Specialty Products

USA, Inc

GP 2000™ - COATINGS REMOVER

(Patent Pending)

Heavy duty viscous, solvent-based replacement for Acetone, MEK, Methylene Chloride and Phenols

INCREASE PRODUCTIVITY:

Extremely effective in removing cured or uncured orthophthalic, isophthalic, cyclopentadiene, vinyl ester and epoxy resins as well as adhesives, pigmented gel coats, high & low solid aliphatic, water-borne epoxy primers, polyurethane, acrylic, varnish and alkyd paints

EASY TO USE:

No heating required. Gel formulation adheres to vertical and horizontal surfaces.

ENVIRONMENTALLY FRIENDLY:

Contains No Hydrocarbon Aromatic Naphtha, Phenols, Butyl Cellosolve, Acetone, MEK, Xylene, Toluene or Methylene Chloride. No heavy metals or ions.

WORKER FRIENDLY:

Non-carcinogenic, non-mutagenic, non-teratogenic and biodegradable.

LOWER INSURANCE PREMIUMS:

It is non-flammable, reduced VOC and contains no ozone depleting chemicals.

WIDE MATERIAL COMPATIBILITY:

Compatible and non corrosive on various metals, plastics, glass and ceramics.

TYPICAL PROPERTIES

pH (50% solution in water @ 68 °F)	6.0 - 7.0	Odor	Mild
Flash Point (°F) (Seta Flash)	188	Viscosity (@ 68 °F) Brookfield Spindle #3, 10 RPM	2000 - 3000
Components Vapor Pressure @ 68 °F [mm Hg]	0.20 - 0.40	Specific Gravity (@ 68 °F)	1.10
Components Boiling Point @ 760 mm Hg (°F)	385 - 485	Weight/Gal. (lbs./gal.)	9.20

CLEANING PROCESS:

Use **GP 2000™ - COATING REMOVER** full strength at room temperature by simply brushing or spraying the surface, remove resins or coatings minutes later.
Do not atomize this product.

SAFETY AND HANDLING PRECAUTIONS:

GP 2000™ - COATINGS REMOVER is a mixture of environmentally safe organic solvents. Although, direct contact can cause a strong skin or eye irritation, it is very important to utilize recommended gloves (18 mm thick natural rubber, neoprene or natural latex), safety goggles and other suitable protective clothing your company recommends. **GP 2000™ - COATINGS REMOVER** is harmful if inhaled or swallowed. Do Not take internally. **Use the product with adequate ventilation.** If splashed in eyes or on skin, wash off with plenty of water. If swallowed remove from exposure area, do not induce vomiting, washout mouth thoroughly with water and drink several glasses of water. Keep at rest. Call a physician immediately. If not already in place, put an emergency shower at work stations if a spill or a line break of **GP 2000™ - COATINGS REMOVER** occurs.

DISPOSAL:

Solutions containing hazardous or non hazardous coatings and other soils should be handled and treated according to Federal, State and Local Environmental Laws. Even though **GP 2000™ - COATINGS REMOVER** is biodegradable, the spent material should not be disposed of in any sewerage system. Discharge your waste and rinse water according to Federal, State and Local Regulations.

STORAGE/PACKAGING:

Packaged in Carbon Steel 1020, 5 gallon pails and 55 gallon drums.
Store in a dry area. Do not freeze.

HMIS RATING:

Health 2 Fire 2 Reactivity 0

**NOW OBTAIN EFFECTIVE CLEANING WITHOUT
DANGEROUS SOLVENTS.**

Global Specialty Products - USA, Inc.
10 Eagle Avenue, Suite 500 - Mount Holly, New Jersey 08060-1649
Phone: 609-518-7577 Fax: 609-518-5277 www.gsp-usa-inc.com