



Global Specialty Products

USA, Inc

OPTIMATM - 2001 CR **CARBON REMOVER & DEGREASER - ZERO VOC**

EXTENDED BATH LIFE - INCREASE PRODUCTIVITY:

Extremely effective in removing **carbon, dirt, oils and various soils** from ferrous and non ferrous metals, polycarbonate plastics and glass substrates.

SOILS REMOVED:

Carbon, Dirt, Oils	Crater & Lithium Grease
Grinding, Finishing & Polishing Compounds	Finger Prints & Particles
Water/Solvent Based Inks	Sulfur Based Cutting Fluids
Automotive, Mineral Vegetable & Polybutane Oils	Lapping & Drawing Compounds
Cosmolines, Lipstick & Cycloparaffins	Adhesives

EASY TO USE - NO RESIDUES FOLLOWING RINSE:

Use full strength or dilute down with water 10 - 50% by volume, easy to rinse. Suitable for use in spray, spray under immersion, ultrasonic agitation or tumblers.

ENVIRONMENTALLY FRIENDLY - NON FLAMMABLE - BIODEGRADABLE:

NO Mineral Spirits, Phenols, TCE, Acetone, MEK, Xylene, Toluene or Methylene Chloride

No SARA Title 313 or HAPPS Reporting
Minimum safety, handling & storage is required

ENVIRONMENTAL & WORKER FRIENDLY:

Non-carcinogenic, non-mutagenic, non-teratogenic

LONG TERM RUST PROTECTION - WIDE MATERIAL COMPATIBILITY:

Compatible and non corrosive on various metals, plastics, glass and ceramics.

TYPICAL PROPERTIES

Appearance	Clear Yellow Liquid	Flash Point (°F)	>200
Odor	Mild	Surface Tension (dynes/cm)	24
pH (10% solution in water @ 68 °F)	10.8 - 11.2	Ideal Operating Temp (°F)	72 - 145
pH (Full Strength)	11.3 - 11.7	Ideal Operating Concentration	10 - 50%
Specific Gravity (@ 68 °F)	1.065 - 1.07	Weight/Gal. (lbs. /gal.)	8.9

CLEANING PROCESS:

OPTIMA™ - 2001CR AQUEOUS CARBON REMOVER AND CLEANER is supplied as a liquid concentrate. Use this product diluted down with water 10 - 50% concentration by volume, at an operating temperature range of 72 - 145 °F. Hand wipe, solution spray, mechanical, or ultrasonic agitation is used to enhance the cleaning action. For carbon, dry oil, grease, polymers, adhesives or inks, soak the parts until residues are removed. Parts can be wiped with a damp rag or rinsed off with warm water. Use filtered hot air to dry out the parts. **To obtain a long-term rust protection, use Solo RI™ Aqueous Rust Inhibitor** at 1-2% concentration in the rinse stage.

SUBSTRATE METALS:

OPTIMA™ - 2001CR AQUEOUS CARBON REMOVER AND CLEANER is formulated specifically for cleaning stainless steel, carbon steel and aluminum alloys. However, it is also suitable for cleaning all other ferrous and non-ferrous metals.

DISPOSAL:

Solutions containing hazardous or non hazardous soils should be handled and treated according to Federal, State and Local Environmental Laws. Even though **OPTIMA™ - 2001CR AQUEOUS CARBON REMOVER AND CLEANER** is biodegradable, the spent material should not be disposed of in any sewerage system. The used material should be characterized and discharged according to Federal, State and Local Regulations.

PACKAGING/STORAGE:

Packaged in HDPE UN Rated 5 gallon pails, 55 gallon drums and 275 totes. The product should be kept in its original container above freezing and less than 100 °F. Store drums in a dry area.

HMIS RATING:

Health 1 Fire 0 Reactivity 0

Global Specialty Products - USA, Inc.
10 Eagle Avenue, Suite 500 - Mount Holly, New Jersey 08060-1649
Phone: 609-518-7577 Fax: 609-518-5277 www.gsp-usa-inc.com