



Global Specialty Products

USA, Inc

BOND BREAKER™ - 2000

GRAFFITI REMOVER

**NON-FLAMMABLE, NON-CHLORINATED, NON-AEROSOL
BIODEGRADABLE GRAFFITI REMOVER**

INCREASE PRODUCTIVITY:

Extremely effective in breaking molecular bond between the paint and the surface. It will effectively remove graffiti from metals, walls, stone, brick, traffic signs, granite, telephone stalls, aluminum siding and highway signs.

Safe on Aluminum and its alloys.

EASY TO USE:

No heating required, No residues following cleaning process, just rinse with water.

ENVIRONMENTALLY FRIENDLY:

The product contains NO Phenols, Butyl Cellosolve, Acetone, MEK, Xylene, Toluene, Methylene Chloride, Mineral Spirits or other aromatic/aliphatic hydrocarbons.

LOWER INSURANCE PREMIUMS:

Non-flammable - contains no HAPs Ingredients.

WIDE MATERIAL COMPATIBILITY:

Compatible and non corrosive on various metals, plastics, glass and ceramics.

TYPICAL PROPERTIES

pH (50% solution in water @ 68 °F)	9.90 - 10.0	Odor	Mild
Flash Point (°F) (Cleveland Open Cup)	160	Viscosity (@ 68 °F) Brookfield Spindle #3, 10 RPM	4000-5000
(Tag Closed Cup)	176	Specific Gravity (@ 68 °F)	0.961
Components Vapor Pressure @ 68 °F [mm Hg]	0.2 - 0.40	Weight/Gal. (lbs./gal.)	8.00
Components Boiling Point @ 760 mm Hg (°F)	356 - 396		

CLEANING PROCESS:

BOND BREAKER™ - 2000 Apply full strength at room temperature by brush or low pressure spray on various substrates covered with graffiti, when graffiti is removed, rinse with water.

Do not Heat or use HIGH PRESSURE SPRAY.

SAFETY AND HANDLING PRECAUTIONS:

BOND BREAKER™ - 2000 Is a mixture of environmentally safe organic solvents. Although, direct contact can cause a strong skin or eye irritation, it is very important to utilize recommended gloves (18 mm thick natural rubber, neoprene or natural latex), safety goggles and other suitable protective clothing your company recommends. **BOND BREAKER™ - 2000** is harmful if inhaled or swallowed. Do Not take internally. Use the product with an adequate ventilation. If splashed in eyes or on skin, wash off with plenty of water. If swallowed remove from exposure area, do not induce vomiting, washout mouth thoroughly with water and drink several glasses of water. Keep at rest. Call a physician immediately. If not already in place, put an emergency shower at work stations if a spill or a line break of **BOND BREAKER™ - 2000** occurs. **Refer to MSDS for more information.**

DISPOSAL:

Solutions containing hazardous or non hazardous soils should be handled and treated according to Federal, State and Local Environmental Laws. Even though **BOND BREAKER™ - 2000** is biodegradable, the spent material should not be disposed of in any sewerage system. Discharge your spent material according to Federal, State and Local Regulations.

STORAGE:

Ordinary Stainless Steel 304 and 316, Carbon Steel 1020 are suitable.
Store drums in a dry area.

HMIS RATING:

Health 1 Fire 2 Reactivity 0

**NOW OBTAIN EFFECTIVE CLEANING
WITHOUT DANGEROUS SOLVENTS**