



Global Specialty Products

USA, Inc

GLOBE KLEEN™ - 2002 “THIXOTROPIC” COATINGS REMOVER

**ELIMINATES
ACETONE, MEK & METHYLENE CHLORIDE**

GET MAXIMUM SAFETY AND IMPROVED PERFORMANCE:

Extremely effective in removing cured or uncured polyester, vinyl ester, epoxy, polyurethane foam and other coatings from tanks, totes, tools as well as other plant and maintenance equipment.

EASY TO USE:

No heating required, No residues following cleaning process.

ENVIRONMENTALLY FRIENDLY:

Contains NO Phenols, Acetone, MEK, Xylene, Toluene, Methylene Chloride, Mineral Spirits or other Aromatic/Aliphatic Hydrocarbons.
NO SARA 313 or HAPPS reporting

LOWER INSURANCE PREMIUMS:

Non-flammable contains no ozone depleting chemicals.

WIDE MATERIAL COMPATIBILITY:

Compatible and non corrosive on various metals, glass and ceramics.

TYPICAL PROPERTIES

pH (50% solution in water @ 68 °F)	9.90 - 10.0	Odor	Mild
Flash Point (°F) (Cleveland Open Cup)	160	Viscosity (@ 68 °F) Brookfield Spindle #3, 10 RPM	4000 - 5000
(Tag Closed Cup)	176		
Components Vapor Pressure @ 68 °F [mm Hg]	0.20 - 0.40	Specific Gravity (@ 68 °F)	0.961
Components Boiling Point @ 760 mm Hg (°F)	356 - 396	Weight/Gal. (lbs./gal.)	8.0

CLEANING PROCESS:

Apply **GLOBE KLEEN™ - 2002** full strength at room temperature by brush or low pressure spray on totes, tanks or other maintenance equipment. Scrape off foam, resin, paint or coatings minutes later. Parts can be wiped with a damp rag. **Do not Heat or Atomize this product.**

SAFETY AND HANDLING PRECAUTIONS:

GLOBE KLEEN™ - 2002 is a mixture of environmentally safe organic solvents. Although, direct contact can cause a strong skin or eye irritation, it is very important to utilize recommended gloves (18 mm thick natural rubber, neoprene or natural latex), safety goggles and other suitable protective clothing your company recommends. **GLOBE KLEEN™ - 2002** is harmful if inhaled or swallowed. Do Not take internally. Use the product with an adequate ventilation. If splashed in eyes or on skin, wash off with plenty of water. If swallowed remove from exposure area, do not induce vomiting, washout mouth thoroughly with water and drink several glasses of water. Keep at rest. Call a physician immediately. If not already in place, put an emergency shower at work stations if a spill or a line break of **GLOBE KLEEN™ - 2002** occurs. **Refer to MSDS for more information.**

DISPOSAL:

Solutions containing hazardous or non hazardous soils should be handled and treated according to Federal, State and Local Environmental Laws. Even though **GLOBE KLEEN™ - 2002** is biodegradable, the spent material should not be disposed of in any sewerage system. Discharge your spent material according to Federal, State and Local Regulations.

STORAGE/PACKAGING:

Packaged in Carbon Steel 1020, 5 gallon pails and 55 gallon drums. Store drums in a dry area. Do not freeze.

HMIS RATING:

Health 1 Fire 2 Reactivity 0

**NOW ACHIEVE ONE-STEP COATING REMOVAL AND
LOW VOC EMISSIONS.**

11272001